

Superior Industries, Inc.

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Material Identification

Product Name: FAST TRACK EPOXY PRIMER PART R
Product Use: Paint product.
Print date: 19/April/2009
Revision Date: 19/April/2009

Company Identification

Superior Industries, Inc.
6180 Airways Blvd.
Chattanooga, TN 37421
Manufacturer's Phone: 1-423-899-0467

24-Hour Medical Emergency Phone
800-476-2972; International: 423-899-0467

2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Common Name CAS-No. | Approx. Weight % | Chemical name |
|------------------------|---------------------|-------------------|
| MODIFIED EPOXY RESIN | 60 - 100 | EPOXY RESIN BLEND |

If this section is blank there are no hazardous components per OSHA guidelines.

3. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Emergency Overview:

This section not in use.

This product contains ingredients that may contribute to the following potential acute health effects:

Inhalation Effects:

May cause respiratory tract irritation. May cause respiratory tract sensitization.

Eye Contact:

May cause moderate eye irritation.

Skin Contact:

May cause skin irritation. Contains a component which is a known or suspected skin sensitizer.

Acute Ingestion:

May be fatal if swallowed.

Other Effects:

None known

This product contains ingredients that may contribute to the following potential chronic health effects:

Possible sensitization.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

4. FIRST AID MEASURES

Inhalation:

If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention.

Eye Contact:

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Skin Contact:

Remove contaminated shoes and discard. Remove contaminated clothing and launder before reuse. In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention.

Ingestion:

If swallowed, get medical attention immediately.

Medical conditions aggravated by exposure: Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|----------------------------------|--|
| Flash point (Fahrenheit): | 201° F (94° C) TCC/PM |
| Lower explosive limit: | Not available. % |
| Upper explosive limit: | Not available. % |
| Autoignition temperature: | Not available. ° F (° C) |
| Sensitivity to impact: | No. |
| Sensitivity to static discharge: | Sensitivity to static discharge is not expected. |
| Hazardous combustion products: | See Section 10. |

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Use water spray to cool nearby containers and structures exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Avoid all personal contact.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep container closed when not in use.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

Skin protection:

Gloves: Neoprene or other nonporous. Neoprene or plastic apron and protective clothing covering exposed skin areas.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Required when spraying or applying in confined area.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

ACGIH Threshold Limit Value (TLV's)

If this section is blank, no information is available.

9. PHYSICAL PROPERTIES

| | |
|---|-------------------------------|
| Odor: | Normal for this product type. |
| Physical State: | Liquid |
| pH: | Not determined. |
| Vapor pressure: | 1 mmHG @ 68° F (20° C) |
| Vapor density (air = 1.0): | Not determined. |
| Boiling point: | 626° F (330° C) |
| Solubility in water: | Insoluble. |
| Coefficient of water/oil distribution: | Not determined. |
| Density (lbs per US gallon): | 9.14 |
| Specific Gravity: | 1.1 |
| Evaporation rate (butyl acetate = 1.0): | Not determined. |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------------|-------------------------------------|
| Stability: | Stable |
| Conditions to Avoid: | None known. |
| Incompatibility: | None known. |
| Hazardous Polymerization: | None anticipated. |
| Hazardous Decomposition Products: | Carbon monoxide and carbon dioxide. |

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

11. TOXICOLOGICAL INFORMATION

Mutagens:

Teratogens:

Carcinogens:

If this section is blank, no information is available.

12. ECOLOGICAL DATA

Not available at this time.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

Proper Shipping Name: PAINT, NOT REGULATED
UN ID Number: NRPAIN

49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity or "does not sustain combustion" exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

International Air Transport Association:

Proper Shipping Name: PAINT, NOT REGULATED
UN ID Number: NRPAIN

International Maritime Organization:

Proper Shipping Name: PAINT, NOT REGULATED
Non-Bulk UN ID Number: NRPAIN

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

SARA 311/312 Hazard Class:

Acute: Yes
Chronic: Yes
Flammability: No
Reactivity: No
Sudden Pressure: No

U.S. STATE REGULATIONS:

Pennsylvania Right To Know:

PROPRIETARY RESIN Trade Secret
PROPRIETARY RESIN Trade Secret

Rule 66 status of product Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

16. OTHER INFORMATION

HMIS Codes

| | |
|---------------|----|
| Health: | 2* |
| Flammability: | 1 |
| Reactivity: | 0 |
| PPE: | C |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The information contained in this Material Safety Data Sheet applies only to the actual Superior Corporation ("Superior") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Superior product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Superior believes to be reliable as of the date hereof. Prior to each use of any Superior product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Superior product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SUPERIOR MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SUPERIOR SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Superior Industries, Inc.

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Material Identification

Product Name: FAST TRACK EPOXY PRIMER PART H
Product Use: Paint product.
Print date: 18/April/2009
Revision Date: 18/April/2009

Company Identification

Superior Industries, Inc.
6180 Airways Blvd.
Chattanooga, TN 37421
Manufacturer's Phone: 1-423-899-0467

24-Hour Medical Emergency Phone
800-476-2072; International: 423-899-0467

2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Common Name CAS-No. | Approx. Weight % | Chemical name |
|------------------------|---------------------|----------------------|
| AMINE ADDUCT | 40 - 70 | MANNICH BASED ADDUCT |

If this section is blank there are no hazardous components per OSHA guidelines.

3. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Emergency Overview:

This section not in use.

This product contains ingredients that may contribute to the following potential acute health effects:

Inhalation Effects:

Causes moderate respiratory irritation. Exposure to mists or vapors may cause irritation of the respiratory tract.

Eye Contact:

Causes severe eye irritation

Skin Contact:

Causes moderate skin irritation.

Acute Ingestion:

Harmful if swallowed.

Other Effects:

None known

This product contains ingredients that may contribute to the following potential chronic health effects:

Repeated and/or prolonged exposure may result in adverse respiratory effects (such as cough, tightness of chest, or shortness of breath). Prolonged or repeated exposure may cause conjunctivitis. May cause eye damage and pain. Prolonged and/or repeated contact can result in skin irritation.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

4. FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Eye Contact:

Flush with plenty of low pressure water for 15 minutes, occasionally lifting eye lids. If irritation persists, consult a physician.

Skin Contact:

Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes. In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention. Destroy contaminated leather apparel.

Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Medical conditions aggravated by exposure: Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|----------------------------------|--|
| Flash point (Fahrenheit): | 225° F (107° C) TCC/PM |
| Lower explosive limit: | Not available. % |
| Upper explosive limit: | Not available. % |
| Autoignition temperature: | Not available. ° F (° C) |
| Sensitivity to impact: | No. |
| Sensitivity to static discharge: | Sensitivity to static discharge is not expected. |
| Hazardous combustion products: | See Section 10. |

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Use water spray to cool nearby containers and structures exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate area. Remove spills with inert absorbent. Avoid all personal contact.

7. HANDLING AND STORAGE

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep container closed when not in use. Keep from freezing. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

Skin protection:

Appropriate chemical resistant gloves should be worn. To prevent skin contact wear protective clothing covering all exposed areas.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Required when spraying or applying in confined area.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

ACGIH Threshold Limit Value (TLV's)

If this section is blank, no information is available.

9. PHYSICAL PROPERTIES

| | |
|---|-------------------------------|
| Odor: | Normal for this product type. |
| Physical State: | Liquid |
| pH: | Not determined. |
| Vapor pressure: | 24 mmHG @ 68° F (20° C) |
| Vapor density (air = 1.0): | .6 |
| Boiling point: | 212° F (100° C) |
| Solubility in water: | Soluble |
| Coefficient of water/oil distribution: | Not determined. |
| Density (lbs per US gallon): | 8.99 |
| Specific Gravity: | 1.08 |
| Evaporation rate (butyl acetate = 1.0): | .4 |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------------|--|
| Stability: | Stable |
| Conditions to Avoid: | None known. |
| Incompatibility: | Avoid water-reactive materials, heat or contact with peroxides or other catalysts. |
| Hazardous Polymerization: | None anticipated. |
| Hazardous Decomposition Products: | Nitrogen compounds. |

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

11. TOXICOLOGICAL INFORMATION

Mutagens:

Teratogens:

Carcinogens:

If this section is blank, no information is available.

12. ECOLOGICAL DATA

Not available at this time.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

Proper Shipping Name: PAINT, NOT REGULATED
UN ID Number: NRPAIN

49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity or "does not sustain combustion" exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

International Air Transport Association:

Proper Shipping Name: PAINT, NOT REGULATED
UN ID Number: NRPAIN

International Maritime Organization:

Proper Shipping Name: PAINT, NOT REGULATED
Non-Bulk UN ID Number: NRPAIN

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

SARA 311/312 Hazard Class:

Acute: Yes
Chronic: Yes
Flammability: No
Reactivity: No
Sudden Pressure: No

U.S. STATE REGULATIONS:

Additional Non-Hazardous Materials

WATER

7732-18-5

Rule 66 status of product

Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

Not all components in this product are listed on the Domestic Substances List.

16. OTHER INFORMATION

HMS Codes

| | |
|----------------------|----|
| Health: | 2* |
| Flammability: | 1 |
| Reactivity: | 1 |
| PPE: | D |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPCCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The information contained in this Material Safety Data Sheet applies only to the actual Superior ("Superior") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Superior product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Superior believes to be reliable as of the date hereof. Prior to each use of any Superior product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Superior product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SUPERIOR MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SUPERIOR SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.