

MATERIAL SAFETY DATA SHEET

VISION KOTE 99

06-21-09

SECTION I

PRODUCT AND MANUFACTURER IDENTIFICATION.

Trade name: VISION KOTE 99 (ALL COLORS)

Product Code: 6601 - 6610

Emergency Phone: (800) 476-2072

Information Phone (423) 899-0467

Manufacturer: Superior Industries, Inc. 6180 Airways Blvd. Chattanooga, TN 37421

SECTION II

HAZARDOUS INGREDIENTS.

Ingredient(s)	CAS No.	Exposure Limits	
		TLV	PEL
Barium Sulfate	7727-43-7	10 mg / m3	5.0 mg/m3
Silica	14808-60-7	.1 mg / m3	.1 mg / m3
Butyl Cellosolve	111-76-2	50 ppm	25 ppm
Diacetone Alcohol	123-42-2	50 ppm	50 ppm

Notes:

- "TLV" means the Threshold Limit Value exposure (8-hour time weighted average unless otherwise noted) established by ACGIH.
- "PEL" refers to the Permissible Exposure Limits for airborne contaminants as specified in 29 CFR 1900-1000.
- "NE" indicates that neither a TLV nor OSHA Permissible Exposure Limit has been established.

SECTION III

PHYSICAL PROPERTIES

INITIAL BOILING POINT: 212 ½ °F	SPECIFIC GRAVITY (H2 O=1): 1.39
VAPOR DENSITY: Heavier than air	SOLUBILITY IN WATER: Soluble
FREEZING POINT: 32 ½ F	pH: 9.5
APPEARANCE AND ODOR: Viscous liquid with a mild ammonia odor	VOC: 180 g/l max.
	EVAPORATION RATE: Slower than n-Butyl Acetate

SECTION IV

FIRE AND EXPLOSION HAZARD

FLASH POINT °F (Tag Closed Cup): None
 FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A
 EXTINGUISHING MEDIA: N/A
 SPECIAL FIRE FIGHTING PROCEDURES: N/A
 FIRE & EXPLOSIVE HAZARDS: NONE

SECTION V

REACTIVITY DATA:

STABILITY Stable
 CONDITIONS TO AVOID: Oxidizes and strong alkalis
 HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Fire conditions may yield oxides of carbon
 HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI

HEALTH HAZARD INFORMATION:

EFFECTS OF OVEREXPOSURE - AVENUE OF ENTRY:
 EYES: Contact with liquid irritate eyes
 SKIN: Possible irritation for sensitive individuals
 INHALATION: Vapors could cause irritation of eyes and nose in some individuals.
 SWALLOWING: Ingestion of large amounts could give toxic effects

FIRST AID:

IF IN EYES: Immediately flush eyes with copious amounts of water.
 IF ON SKIN: Wash affected area thoroughly with soap and water
 IF INHALED: Remove to fresh, room temperature air
 IF SWALLOWED: Do not induce vomiting. Call physician or hospital emergency room. Do not attempt to give anything by mouth to an unconscious person

SECTION VII

SPILL OR LEAK PROCEDURES.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dilute and absorb spill with inert material (sand, etc.) and dispose of suitably

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

PRECAUTIONS TO TAKE IN STORAGE AND HANDLING: This product should be kept from freezing during shipping and handling. Although freezing represents no hazard, it may ruin the product

OTHER PRECAUTIONS: This product contains trace amounts of aqueous ammonia and slight traces of residual acrylic monomers and formaldehyde carried in with the acrylic latex polymer and surfactant used. These trace levels are below reporting requirements in the hazardous components Section II. Although these are toxic chemicals, at these trace levels they should produce no harmful effects if this product is handled with normal care and caution. **CAUTION: KEEP OUT OF REACH OF CHILDREN**

=====SECTION VIII

SAFE HANDLING AND USE INFORMATION:

RESPIRATORY PROTECTION: Self-contained breathing apparatus for concentrations above TLV limits

VENTILATION: General ventilation

PROTECTIVE GLOVES: Gloves impervious to water based materials

EYE PROTECTION: Splash proof goggles

OTHER PROTECTIVE EQUIPMENT: Apron, work clothes, etc.

HYGIENIC PRACTICES: After using product, wash hands with soap and water

=====SECTION IX

DISCLAIMER:

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with Superior or not. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.