

# MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

## SECTION I - PRODUCT IDENTIFICATION

**Product Name:** Zin Kote 601  
**Product Number:** 93475-22  
**Product Type:** AEROSOL  
**Formula:** Proprietary  
**Supplier's Name:** Superior Industries, Inc.  
**Supplier's Address:** P.O. Box 8, Chattanooga, TN 37401  
**DOT Ship Description:** CONSUMER COMMODITY, ORM-D  
**Date Prepared:** 10/19/11  
**Information Phone:** (423) 899-0467  
**Emergency Phone:** (800) 476-2072

### HMIS Rating (Based on Aerosol Conc.):

0-Minimal 1-Slight 2-Moderate

3-Serious 4-Extreme

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	1
Personal Protection:	I

## SECTION II - INGREDIENTS

CHEMICAL NAME	CAS#	%WT	313/Chem	Skin	Carcinogen	PEL	TLV-TWA
Toluene	108-88-3	30-40	YES	YES	NO	200 ppm	50 ppm
Zinc	7440-66-6	10-20	YES	NO	NO	10 mg/m3 (dust)	N/E
Petroleum Distillates, Hydrotreated, Light	64742-47-8	1-10	NO	NO	NO	500 ppm	100 ppm
Liquefied Petroleum Gas	68476-86-8	35-45	NO	NO	NO	1000 ppm	1000 ppm

## SECTION III - PHYSICAL DATA

**Aerosol Concentrate:**  
**Boiling Point:** >200°F  
**pH:** N/A  
**Appearance/Odor:** Gray, viscous liquid with solvent odor.  
**Specific Gravity (H2O=1)@70°F:** 1.105  
**Solubility In Water:** Negligible  
**Vapor Density(Air=1):** >1

**Total Contents:**  
**Total VOC %:** 77.62%  
**Vapor Pressure (can; psig @72°F):** 60

## SECTION IV - FIRE AND EXPLOSION DATA

**Flash Point (Conc.):** 80°F  
**Extinguishing Media:** Foam, CO2, Dry Media  
**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.  
**Unusual Fire and Explosion Hazards:** Exposure to temperature above 120° F may cause bursting.  
**Flammability (as per CSMA Flame Projection Test):** Extremely Flammable Spray

## SECTION V - REACTIVITY DATA

**Stability:** Material Stable.  
**Incompatibility:** Avoid contact with halogen gases, strong oxidizing agents, acids, and alkaline hydroxides.  
**Hazardous Decomposition Products:** Carbon Dioxide, Carbon Monoxide, and Zinc Oxide fume.  
**Hazardous Polymerization:** Will not Occur.

## SECTION VI - STORAGE AND HANDLING

**KEEP OUT OF REACH OF CHILDREN.**  
**NFPA Code 30B Rating:** Level 3 Aerosol.  
For Industrial and Institutional use only.  
Store in a cool, dry area away from heat or open flame.  
Do not store at temperatures above 120° F.

## SECTION VII - HEALTH AND FIRST AID

**PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:**  
**Eyes:** May cause irritation accompanied by stinging, tearing, redness, and swelling of eyes.  
**Skin:** May cause mild irritation. Frequent or prolonged contact may cause redness, burning, and drying and cracking of skin. Passage of this material into the body through the skin is possible. May aggravate existing skin conditions.  
**Inhalation:** Inhalation of small amounts of vapor or mist is not likely to cause harmful effects. Inhalation of large amounts may irritate the upper respiratory tract, cause flu-like symptoms, and have a slight anesthetic effect. Prolonged overexposure can cause central nervous system excitation followed by central nervous system depression and other central nervous system effects, temporary changes in mood and behavior, muscle weakness, loss of coordination, confusion, irregular heartbeat, coma, and death. Intentional, prolonged abuse may lead to damage to the central and peripheral nervous systems, vision, hearing, liver, kidneys, heart, blood, and brain.  
**Ingestion:** Can cause gastrointestinal irritation, nausea, fever, vomiting and diarrhea. Aspiration of material into the lungs can cause lung inflammation and other lung injury.  
**FIRST AID PROCEDURES:**  
**Eyes:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **Skin:** Wash with soap and water. If irritation persists seek medical attention.  
**Inhalation:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **Ingestion:** Do not induce vomiting. Seek medical attention immediately.

## SECTION VIII - SPECIAL PROTECTION DATA

**Respiratory Protection:** If air concentrations exceed exposure limits listed in Section II, wear NIOSH/MSHA approved respirator with dust filter and organic vapor cartridge. **Ventilation:** Provide local exhaust to keep air concentrations of ingredients listed in Section II below acceptable limits.  
**Protective Gloves:** Use chemical resistant gloves to prevent hand contact.  
**Eye Protection:** Always wear safety glasses or chemical proof goggles when working with chemicals.

## SECTION IX - SPILL OR LEAK PROTECTION

**STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:** Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.  
**WASTE DISPOSAL METHOD:** Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

**NOTICE:** The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.

