

MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

Product Name: DRY TRAC (Non-Chlorinated)
Product Number: 95412875
Product Type: AEROSOL
Supplier's Name: Superior Industries, Inc.
Supplier's Address: P.O. Box 8, Chattanooga, TN, 37401
D.O.T. Hazard Class: CONSUMER COMMODITY · ORM-D

Formula: Proprietary
Date Prepared: 10/23/06
Emergency Phone: (800) 476-2072
Information Phone: (423) 899-0421

HMIS Rating (Based on Aerosol Conc.):
0-Minimal 1- Slight 2- Moderate
3- Serious 4- Extreme
HEALTH: 2 **FIRE:** 3 **REACTIVITY:** 0
Personal Protection: B

SECTION II · INGREDIENTS

CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TWA/TLV
Toluene	108-88-3	20-40	YES	YES	NO	200 ppm	50 ppm
Acetone	67-64-1	01-10	NO	NO	NO	1000 ppm	500 ppm
Aliphatic Hydrocarbons	8052-41-3	01-10	NO	NO	NO	500 ppm	100 ppm
Isopropanol	67-63-0	01-10	NO	NO	NO	400 ppm	200 ppm
Liquified Petroleum Gas	68476-86-8	35-45	NO	NO	NO	1000 ppm	1000 ppm

SECTION III · PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only:

Boiling Point: ~ 133° F

pH: N/A

Solubility In Water: Negligible

Appearance/Odor: Dark Gray Viscous Liquid, Solvent Odor

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1)@75°F: 0.937

Data Below Based On Total Contents:

Vapor Pressure of can (psig @70°F): 50

Total VOC %: 83.7%

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (of Concentrate Only): ~48°F

Flammability (as per USA Flame Projection Test): Flammable Spray

Extinguishing Media: Foam, CO₂, Dry Media

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.

SECTION V · REACTIVITY DATA

Stability: Material Stable.

Hazardous Polymerization: Will not Occur.

Incompatibility: Avoid contact with strong oxidizing agents,

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide, Sulfur Oxides.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F.

NFPA Code 30B Rating: Level 3 Aerosol.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause moderate to severe eye irritation. Symptoms include stinging, tearing, redness, blurred vision, and swelling of eyes.

Skin: May cause mild to moderate irritation. Frequent or prolonged contact may dry and cause defatting of the skin and possibly dermatitis. Symptoms may include redness, burning, drying and cracking of skin, and even skin burns. Passage of this material through the skin is possible but it is unlikely to result in harmful effects during safe handling and use. May aggravate existing skin conditions.

Inhalation: Inhalation of vapor or mist can cause irritation of nasal and respiratory passages. Prolonged or repeated inhalation may cause headache, dizziness, nausea, muscle weakness, irregular heartbeat, rapid breathing, narcosis, unconsciousness, and other central nervous system effects, possibly including coma and death. Repeated overexposure may injure or cause damage to the liver, kidneys, lungs, heart, bloodstream, and brain. Intentional abuse could cause hearing loss and deafness.

Ingestion: Can cause gastrointestinal irritation, nausea, and vomiting. Aspiration of material into the lungs can cause lung inflammation and other lung injury.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions. If ventilation is not adequate to reduce vapors below Threshold Limit Value (TLV) levels, use a NIOSH/MSHA approved air-purifying respirator equipped with an organic vapor cartridge.

Ventilation: Provide local exhaust to keep air concentrations of ingredients listed in Section II ingredients allowable limits.

Protective Gloves: Use chemical resistant gloves if hand contact will be made.

Eye Protection: Wear safety glasses or chemical proof goggles.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.