SAFETY DATA SHEET

Superior Industries, Inc. SDS SERIES

NT-OG 100 | Food Grade Open Gear Lubricant

Revision A

Effective Date: 3/3/2017 Regulation: 1907/2006/EC, In accordance with the provisions of Article 41, Industrial Safety & Health Act. OSHA Hazard Communication Standard (29 CFR 1910.1200).

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER

	100 #00, NT-OG 100 #0,	,	NT-OG 100 #1.5
Product Code : 06617	06619	06620	06621
1.2 RELEVANT IDENTIFIED	USES OF THE SUBSTA	NCE OR MIXTUR	RE AND USES ADVISED AGAINST
Product Use Uses Advised Against		not be used in ap	plications other than those first seeking the advice of the supplier.
1.3 DETAILS OF THE SUPP	LIER OF THE SAFETY D/	ATA SHEET	
Manufacturer/Supplier	: Superior Industries 6180 Airways Blvd. Chattanooga, TN 37		
Telephone	: Marketing Technicia 1(800) 476-2072, (42)	•	
Fax	: (423) 899-0421		

1.4 EMERGENCY TELEPHONE NUMBER : 1.800.476.2072 International – 423.899.0467

2. HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

1999/45/EC and OSHA 29 CFR 1910.1200	
Hazard Characteristics	R-phrase(s)
Not classified as dangerous under EC Criteria	
Hazard Not Otherwise Classified (HNOC)	

2.2 EC LABEL ELEMENTS Labeling according to Directive 1999/45/EC

EC Classification	: Not classified as dangerous substance.
EC Symbols	: No Hazard Symbol required.
EC Risk Phrases	: Not classified.
EC Safety Phrases	: Not classified.
Health Hazard	: Not expected to be a health hazard when used under normal conditions.
Environmental Hazards	: Not classified as dangerous for the environment.

2.3 GHS LABEL ELEMENTS

GHS Classification	: Not classified as dangerous substance.
GHS Symbol(s)	: No symbol.
GHS Signal Words	: No signal word.
Physical Hazards	: Not classified.
Health Hazards	: Not classified.
Environmental Hazards	: None
GHS Precautionary Statemen	ts
Prevention	: Avoid release to environment.
Response	: No Precautionary phrases.
Storage	: No Precautionary phrases.
Disposal	: Dispose of contents and container to appropriate waste site or reclaimed in accordance with local and national regulations.
2.4 OTHER HAZARDS	
Unclassified Hazards Health	: Prolonged or repeated skin contact without proper cleaning can clog pores of skin resulting in disorders such as oil acne/folliculitis. High-pressure injection under the skin may cause serious damage including local necrosis. Used grease may contain harmful

: Not classified as flammable, but will burn.

Safety

3. COMPOSITION/INFORMATION ON INGREDIENTS

impurities.

3.1 SUBSTANCE

Material Name : Not applicable.

3.2 MIXTURES

Mixture Description : A lubricating non-toxic grease consisting of synthetic oil and additives.

Chemical Identity	Name	CAS	Hazard Class
Synthetic Hydrocarbon Base Oil	1-Decene, Homopolymer, Hydrogenated	68037014	None
Hydrophobic Silica	Hydrophobized highly dispersed silica, synthetic, x-ray amorphous silicon dioxide	67762-90-7	None

Additional Information : This mixture does not contain any REACH registered substances that are assessed to be PBT or a vPvB.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage of composition may have been withheld.

4. FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

General Information	: Not expected to be a health hazard when used under normal conditions.
Inhalation	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. If persistent irritation occurs, obtain medical attention. Obtain medical attention even in absence of apparent wounds.
Eye Contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	: In general no treatment is necessary unless large quantities are swallowed; however, seek medical advice.

Self-protection

of the first aider : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS

Acute and Delayed : Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Note to Physician : Treat symptomatically. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy to minimize tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anesthetics, and wide exploration is essential.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

5.1 EXTINGUISHING MEDIA:

Foam, water spray, or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Hazardous combustion products may include: a complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

5.3 ADVICE FOR FIREFIGHTERS:

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product. Self-contained breathing apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. Observe the relevant local and international regulations.

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

For non-emergency personnel	: Avoid contact with skin and eyes.
For emergency responders	: Avoid contact with skin and eyes.

6.2 ENVIRONMENTAL PRECAUTIONS:

Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth or other appropriate barriers.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.

6.4 REFERENCE TO OTHER SECTIONS:

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

7. HANDLING AND STORAGE

7.1 GENERAL PRECAUTIONS:

Use local exhaust ventilation if there is risk of inhalation of vapors, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2 PRECAUTIONS FOR SAFE HANDLING:

Avoid prolonged or repeated contact with skin. Avoid inhaling vapors and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

7.3 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage Recommended Materials Unsuitable Materials	 Store at ambient temperature. For containers or container linings, use mild steel or high density polyethylene. PVC. 	
7.4 SPECIFIC END USE(S) Additional Information	: Not applicable. : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.	

Refer to Section 15 for any additional specific legislation covering the packaging and storage of this product.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

8.1 CONTROL PARAMETERS

Occupational Exposure Limits

Material	Source	Туре	PPM	mg/m³	Notation
Oil Mist 1-Decene,	ACGIH	TVL (inhalation fraction)		5	
Hydropolymer, Hydrogenated	OSHA	PEL		5	
	ACGIH	TWA (Inhalable fraction)		10	
Silica, amorphous	ACGIH	TWA (Respirable fraction)		3	
	OSHA	PEL		0.8	

Additional Information

: Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Biological Exposure Index (BEI)
PNEC Related Information

: No biological limit allocated.

: Data not available.

Monitoring Methods: Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances, biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analyzed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA:	Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung	
Manual of Analytical Methods http://www.cdc.gov/niosh/	(IFA), Germany <u>http://www.dguv.de/inhalt/index.jsp</u>	
Occupational Safety and Health Administration (OSHA), USA: Sampling	L'Institut National de Recherche et de Securité, (INRS), France	
and Analytical Methods http://www.osha.gov/	http://www.inrs.fr/accueil	
Health and Safety Executive (HSE), UK: Methods for the		
Determination of Hazardous Substances http://hse.gov.uk/		

8.2 EXPOSURE CONTROLS

General Information:

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Occupational Exposure Controls

Personal Protective Equipment:

The provided information is made in consideration of the PPE directive (Council Directive 89686EEC) and the CEN European Committee for Standardization (CEN) standards. Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye Protection:

Wear safety glasses or full face shield if splashes are likely to occur. Approved to EU Standard EN166.

Hand Protection:

Where hand contact with the product may occur, the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time or more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor or glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Body Protection:

Skin protection not ordinarily required beyond standard issue work clothes.

Respiratory Protection:

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapors [boiling point > 65°C (149°F)] meeting EN14387.

Thermal Hazards : Not applicable.

Environmental Exposure Controls Measures:

Minimize release to the environment. An environment assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in Section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical Description	: Clear, semi-solid, tacky	N-Octanol/Water Partition	: > 6 (based on information on similar
рН	: NDA		products) coefficient (log Pow)
Boiling Point	: N/A	Dynamic Viscosity	: NDA
Dropping Point	: None	Kinematic Viscosity	: 23 cSt @ 100°C
Flash Point (COC)	: 231-288°C (448-550°F) min.	Vapor Density (Air = 1)	: > 1 (estimated value)
Water Solubility	: Insoluble	Evaporation Rate (nBuAc = 1)	: NDA
Auto-Ignition Temp.	: None	Decomposition	: NDA
Specific Gravity	: 0.89-0.90 @ (15.6/15.6C)	Vapor Pressure	: N/A
Relative Density	: Typical 0.9 @ 15°C/59°F	Temperature Flammability	: NDA
Density	: Typical 0.9 kg/m3 @ 15°C/59°F	Oxidizing Properties	: NDA
Upper/Lower Flam.	: Typical 1-10% (V)	Explosive Properties	: Not classified

The

10. STABILITY AND REACTIVITY

10.1 REACTIVITY	: The product does not pose any further reactivity hazards in		
10.2 CHEMICAL STABILITY	addition to those listed in the following sub-paragraph.No hazardous reaction is expected when handled and stored according to provisions.		
10.3 POSSIBILITY OF HAZARDOUS REACTIONS : Reacts with strong oxidizing agents.			
10.4 CONDITIONS TO AVOID	: Extremes of t	emperature and direct sunlight.	
10.5 INCOMPATIBLE MATERIALS	: Strong oxidiz	ing agents.	
10.6 HAZARDOUS DECOMPOSITIC	ON PRODUCTS	: Hazardous decomposition products are not expected to form during normal storage.	

11. TOXICOLOGICAL INFORMATION

11.1 INFORMATION TOXICOLOGICAL EFFECTS

Basis for Assessment	: Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).		
Likely Routes of Exposure	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.		
Acute Oral Toxicity	: Expected to be of low toxicity: LD50 > 5000mg/kg, Rat.		
Acute Dermal Toxicity	: Expected to be of low toxicity: LD50 > 5000mg/kg, Rabbit.		
Acute Inhalation Toxicity	: Not considered to be an inhalation hazard under normal conditions of use.		
Skin Corrosion/Irritation	: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog pores of the skin resulting in disorders such as oil acne/folliculitis. Low toxicity: LD50 >2000 mg/kg, Rabbit.		
Serious Eye Damage/Irritation	: Expected to be slightly irritating.		
Respiratory Irritation	: Inhalation of vapors or mists may cause irritation.		
Respiratory/Skin Sensitization	: Not expected to be a sensitizer.		
Aspiration Hazard	: Not considered an aspiration hazard.		
Germ Cell Mutagenicity	: Not considered a mutagenic hazard.		
Carcinogenicity	: Not expected to be carcinogenic.		
Motorial	Consistence in the Classification		

Material	Carcinogenicity Classification
PCA-Content (IP346 <3%)	ACGIH Group A4: Not classifiable as human carcinogen
PCA-Content (IP346 <3%)	IARC 3: Not classifiable as to carcinogenicity to humans
PCA- Content (IP346 <3%)	GHS/CLP: No carcinogenicity classification

Reproductive & Developmental Toxicity : Not expected to be a hazard.

Summary on Evaluation of the CMR Properties:

Carcinogenicity :	This product does not meet the criteria for classification in categories 1A/1B.		
Mutagenicity :	: This product does not meet the criteria for classification in categories 1A/1B.		
Reproductive Toxicity (fertility) :	: This product does not meet the criteria for classification categories 1A/1B.		
Specific Target Organ (Single exposure)	: Not expected to be a hazard.		
Specific Target Organ (Repeated exposition of the second sec	ure) : Not expected to be a hazard.		

Additional Information : Used grease may contain harmful impurities that have accumulated during use. concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal. ALL used grease should be handled with caution and skin contact avoided as far as possible. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed. Classification by other authorities under carrying regulatory frameworks may exist.

12. ECOLOGICAL INFORMATION

Basis of Assessment	: Eco toxicological data have not been determined specifically for this product. Information given is based on knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).			
12.1 TOXICITY				
Acute Toxicity	: Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically nontoxic: LL/EL/IL50 > 100mg/1 (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous extract.			
12.2 PERSISTENCE & DEGR	ADABILITY	: Expected to not be readily biodegradable.		
12.3 BIO ACCUMULATIVE POTENTIAL		: Not expected to bio accumulate significantly.		
12.4 MOBILITY IN SOIL		: Semi-solid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Sinks in water.		
12.5 RESULT OF PBT & vPvE	3 ASSESSMENT	: This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.		
12.6 OTHER ADVERSE EFFECTS		: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.		

13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Material Disposal : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine to proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.

- **Container Disposal :** Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.
- Local Legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations. EU Waste Disposal Code (EWC): 12 01 12 spent waxes and fats. Classification of water is always the responsibility of the end user.

14. TRANSPORTATION AND OSHA RELATED LABEL INFORMATION

Land Transport (ADR/RID)

- **ADR** : This product is not classified as dangerous for this mode of transport. Therefore REACH requirements of 14.1 UN Number, 14.2 UN Proper shipping name, 14.3 Transport hazard class(es), 14.4 Packing group, 14.5 Environmental hazards, and 14.6 Special precautions for use do not apply.
- **RID** : This product is not classified as dangerous for this mode of transport. Therefore REACH requirements of 14.1 UN Number, 14.2 UN Proper shipping name, 14.3 Transport hazard class(es), 14.4 Packing group, 14.5 Environmental hazards, and 14.6 Special precautions for use do not apply.
- **DOT** : Not regulated for land transportation.
- **TDG** : Not regulated for land transportation.

Inland Waterways Transport (AND): This product is not classified as dangerous for this mode of transport. Therefore REACH requirements of 14.1 UN Number, 14.2 UN Proper Shipping name, 14.3 Transport hazard class(es), 14.4 Packing group, 14.5 Environmental hazards, and 14.6 Special precautions for use do not apply. CDNI Inland Water Waste: NST 3411 Greases Agreement.

- Sea Transport (IDMG CODE) : This product is not classified as dangerous for this mode of transport. Therefore REACH requirements of 14.1 UN Number, 14.2 UN Proper Shipping name, 14.3 Transport hazard class(es), 14.4 Packing group, 14.5 Environmental hazards, and 14.6 Special precautions for use do not apply.
- Air Transport (IATA): This product is not classified as dangerous for this mode of transport.
Therefore REACH requirements of 14.1 UN Number, 14.2 UN Proper shipping
name, 14.3 Transport hazard class(es), 14.4 Packing group, 14.5 Environmental
hazards, and 14.6 Special precautions for use do not apply.

Transport in Bulk According to Annex II of MARPOL 73/78 and IBC Code

Pollution Category	: N/A	Ship Type	: N/A
Product Name	: N/A	Special Precaution	: N/A
		anov 1 rules apply for bully shi	nmonto hucon

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

15.1 SAFETY, HEALTH & ENVIRONMENTA MIXTURE	L REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR
Other Regulatory Information	: Product is not subject to Authorization under REACH.
Authorizations and/or Restrictions on Use	
Recommended Restrictions on Use (Advice Against)	: This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier.
Chemical Inventory Status	
EINECS	: All components listed on polymer exempt.
TSCA	: All components listed.
15.2 CHEMICAL SAFETY ASSESSMENT	: No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Г <u> </u>				
16. OTHER INFORMATION				
NFPA Hazard ID	: Health – C		•	Instability – 0
HMIS Hazard ID	: Health – C) Flammability	y — 1	Reactivity – 0
Additional Information	•			ttached to this Safety Data Sheet as i ng no hazardous substances.
Abbreviations and Acronyms				acronyms used in this document ca re (e.g., scientific dictionaries) and/o
websites.ACGIH = American Conference of Governmental Industrial HygienistsAICS = Australian Inventory of Chemical SubstancesBEL = Biological Exposure LimitsCAS = Chemical Abstract ServiceCLP = Classification Packaging and LabelingDIN = Deutsches Institut fur NormungDNEL = Derived No Effect LevelEC = European CommissionECETOC = European Inventory of Existing Commercial Chemical SubstancesEINECS = European Inventory of Existing Commercial Chemical SubstancesENCS = Japanese Existing and New Chemical Substances InventoryGHS = Globally Harmonized System of Classification and Labeling of ChemicalsIATA = International Air Transport AssociationIL50 = Inhibitory Level FiftyINV = Chinese Chemicals InventoryLD50 = Lethal Loading FiftyNOEC/NOEL = No Observed Effect Concentration/ No Observed Effect LevelPBT = Persistent, Bio accumulative and ToxicPNEC = Predicted No Effect ConcentrationRID = Regulations Relating to International Carriage of Dangerous Goods by RailSTEL = Short Term Exposure Limit		ASTM = American Society BTEX = Benzene, Toulene, CEFIC = European Chemic. COC = Cleveland Open-Cu DMEL = Derived Minimal I DSL = Canada Domestic Su EC50 = Effective Concentr ECHA = European Chemic EL50 = Effective Loading F EWC = European Waste IC50 = Inhibitory Concent IMDG = International Agen IC50 = Inhibitory Concent IMDG = International Mai yclic aromatics DMSO extra LC50 = Lethal Concentrati LL/EL/IL = Lethal Loading/ MARPOL = International C OE_HPV = Occupational E	for Testing Eythlbenzz P Effect Leve Ubstance Li ation Fifty als Agency ifty ode ccy for Rese ration Fifty ritime Dan uctables on Fifty Effective L ionvention xposure-Hi ry of Chen uation & A ion ment	ene, Xylenes al Council el ist earch on Cancer / gerous Goods oading/Inhibitory Loading for the Prevention of Pollution from Ships igh Pollution Volume nicals and Chemical Substances

Additional Abbreviations and Acronyms:

Acute Tox. = Acute Toxicity	Asp Tox. = Aspiration Toxicity
Aquatic Acute = Acute hazards to the aquatic environment	Aquatic Chronic = Long-term hazard to the aquatic environment
Eye Dam. = Serious eye damage/eye irritation	Flam. Liq. = Flammable liquids
Skin Corr. = Skin corrosion irritation	Skin Sens. = Skin sensitization
STOT Se = Specific target organ toxicity- single exposure	STOT Re = Specific target organ toxicity- repeated exposure

SDS Distribution	: The information in this document should be made available to all who may handle the product.
SDS Revision Number	: A
SDS Effective Date	: 03/3/2017
SDS Regulation	: Regulation 1907/2006/EC as amended by Regulation (EU) 453/2000. In accordance with the provisions of Article 41, Industrial Safety & Health Act and OSHA Hazard Communication Standard (29 CFR 1910.1200).
Disclaimer	: The information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.