MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

Product Name: ATL #400 Product Number: 2492 Product Type: AEROSOL

Supplier's Name: Superior Industries, Inc.

Supplier's Address: P.O. Box 8, Chattanooga, TN 37401 D.O.T. Hazard Class: CONSUMER COMMODITY ORM-DA Formula: Proprietary Date Prepared: 1F/€J⊕G

Emergency Phone: (800) 476-2072 Information Phone: (423) 899-0467

Vapor Density(Air=1): >1

Specific Gravity (H2O=1)@75°F: 0.757Á

Flammability (as per USA Flame Projection Test): Extremely-Flammable SprayÁ

HMIS Rating (Based on Aerosol Conc.);Á 1- Slight 2- Moderate Á 0-Minimal

3- Serious 4- ExtremeÁ HEALTH: 1 FIRE: 3 REACTIVITY: 0Á Personal Protection: BÁ

SECTION II · INGREDIENTS

CHEMICAL NAME	CAS#	%WT	313/Chem	Skin	Carcinogen	PEL	TWA/TLV	•
Isoparaffinic Hydrocarbon Petroleum Hydrocarbon Isopropanol	64742-66-8 64742-53-6 67-63-0	50-60 10-20 01-10	NO NO NO	NO NO NO	NO NO NO	N/E 5 mg/m3 400 ppm	281 ppm* 5 mg/m3 200 ppm	Á Á
Liquefied Petroleum Gas	68476-86-8	10-30	NO	NO	NO	1000 ppm	1000 ppm	Á

^{*}Manufacturer's Recommended Exposure Limit (TWA)Á

SECTION III · PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only:

Boiling Point: ~180° FÁ

pH: N/A

Solubility In Water: Insoluble

Appearance / Odor: Red Liquid, Solvent OdorÁ Data Below Based On Total Contents: Vapor Pressure of can (psig @70°F): 55Á

Total VOC %: ~ 81.6%Å

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (of Concentrate Only): ~45° F (T.C.C.)

Extinguishing Media: Foam, CO2,

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing. A

Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.Á

SECTION V · REACTIVITY DATA

Stability: Material Stable. Hazardous Polymerization: Will not Occur.Á

Incompatibility: Avoid contact with strong oxidizing agents.Á

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide.Á

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN."

For Industrial and Institutional use only.Á

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F

NFPA Code 30B Rating: Level 3 Aerosol. Á

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause irritation accompanied by stinging, tearing, redness, and swelling.

Skin: Frequent or prolonged contact may cause irritation and possibly dermatitis. May aggravate existing skin conditions.A

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the respiratory tract, dizziness, nausea, low blood pressure, lung edema, kidney damage, and other central nervous system effects, including unconsciousness and death. A

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion of large amounts may cause mild, reversible liver effects. Aspiration of material

into the lungs can cause mild to severe pulmonary injury. Á

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **/\$kin**: Wash with soap and water. If irritation persists seek medical attention A

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. Á

Ingestion: Do not induce vomiting. Seek medical attention immediately.Á

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions. Á

Ventilation: Provide local exhaust to keep air concentrations of ingredients listed in Section II below established limits. Á

Protective Gloves: Use chemical resistant gloves if hand contact will be made.Á

Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.. Á

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in awceraawce lith Federal, Itete Ind locaw laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, Á State and local authorities for approved procedures.Á

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product. A