

***** SECTION 1: PRODUCT IDENTIFICATION *****

MANUFACTURERS ADDRESS : 6180 Airways Blvd.,, Chattanooga,Tn 37421
MFG TELEPHONE NUMBER : (423) 899-0467
24 HR EMERGENCY PHONE NO : 1-800-476-2072
CHEMICAL NAME OR FAMILY : COATINGS PRODUCT
FORMULA : NOT APPLICABLE
TRADE NAME : Re-Surf Part A Hardner
REVISION DATE : 11-09-12
DATE PRINTED : 11-09-12

***** SECTION 2: HAZARDOUS INGREDIENTS *****

NAME	WT %				
COMMON(NA) : PROPRIETARY ADDITIVE		TLV TWA	NOT ESTAB		
CAS: TRADE SECRET		TLV STEL	NOT ESTAB		
		OSHA PEL	NOT ESTAB		
		CEILING	NOT ESTAB		
		RECOMND	NOT ESTAB		
COMMON(NA) : PINE OIL	5-10%	TLV TWA	NOT ESTAB		
CAS: 8002-09-3	CHEMICAL: OILS, PINE	TLV STEL	NOT ESTAB		
		OSHA PEL	NOT ESTAB		
		CEILING	NOT ESTAB		
		RECOMND	NOT ESTAB		

THERE ARE NO SARA 313 CHEMICALS IN THIS PRODUCT

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH U.S. TSCA CHEMICAL SUBSTANCE INVENTORY REQUIREMENTS.

***** SECTION 3: PHYSICAL DATA *****

BOILING POINT: 374 DEG F. (190 DEG C.)
VAPOR PRESSURE MM HG AT 77 DEG F. (25 DEG C.): 5.0
VAPOR DENSITY (AIR = 1.0): 4.8
SPECIFIC GRAVITY: 0.98
PERCENT VOLATILE BY VOLUME: 10.50
EVAPORATION RATE (BUTYL ACETATE = 1): 1.0
SOLUBILITY IN WATER: NO
PH : N.AV
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.AV

***** SECTION 4: FIRE AND EXPLOSION HAZARD *****

FLASH POINT TCC/PM DEG F : 200
FLASH POINT TCC/PM DEG C : 93
LOWER EXPLOSIVE LIMIT : 1.00
UPPER EXPLOSIVE LIMIT : 6.00
AUTO IGNITION - DEG F : N.AV DEG C : N.AV
SENSITIVITY TO IMPACT : NONE
SENSITIVITY TO STATIC DISCHARGE : N.AV

EXTINGUISHING MEDIA: IN CASE OF FIRE, USE WATER SPRAY (FOG), ALCOHOL FOAM, DRY CHEMICAL, OR CARBON DIOXIDE.
WATER SPRAY MAY BE USED TO COOL CONTAINERS AND KEEP EXPOSED MATERIAL FROM BEING DAMAGED BY FIRE.

***** SECTION 4: FIRE AND EXPLOSION HAZARD *****CONTINUED*****

SPECIAL FIRE FIGHTING PROCEDURES:

FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS.
CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

CLOSED CONTAINERS MAY EXPLODE DUE TO BUILD UP OF PRESSURE WHEN EXPOSED TO HEAT.

***** SECTION 5: HEALTH HAZARD DATA *****

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:

IMMEDIATE EFFECTS (ACUTE):

REDNESS OR DRYNESS OF SKIN.
HARMFUL IF INHALED. MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RES-
PIRATORY SYSTEM, CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY
IRRITATION.

OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND
THROAT IRRITATION, EYE IRRITATION, SKIN IRRITATION.

DELAYED EFFECTS (CHRONIC):

EYE DAMAGE AND PAIN.

POSSIBLE SENSITIZATION.

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL
OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM
DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY
RESPIRATORY OR SKIN CONDITION.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15
MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER.

CLOTHING: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH CLOTHING
BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED SHOES.

INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE
TO FRESH AIR.

SWALLOWING: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

***** SECTION 6: REACTIVITY DATA *****

THIS PRODUCT IS STABLE
CONDITIONS TO AVOID: NONE
INCOMPATIBILITY: NA

HAZARDOUS DECOMPOSITION PRODUCTS:

AMMONIA COMPOUNDS NITROGEN OXIDES CARBON DIOXIDE/MONOXIDE

HAZARDOUS POLYMERIZATION: NONE

***** SECTION 7: SPILL OR LEAK PROCEDURES

VENTILATE AREA. AVOID BREATHING OF VAPORS. USE SELF-CONTAINED BREATHING APPARATUS OR AIRMASK FOR LARGE SPILLS IN A CONFINED AREA. ELIMINATE IGNITION SOURCES. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. AVOID CONTACT WITH EYES.

WASTE DISPOSAL METHOD:

DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL, STATE, PROVINCIAL AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

***** SECTION 8: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ABOVE APPLICABLE LIMITS, NO RESPIRATOR IS REQUIRED. IF RESPIRATOR IS REQUIRED, THE APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) SHOULD BE WORN DURING APPLICATION. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

VENTILATION:

REQUIRED WHEN SPRAYING OR APPLYING IN CONFINED AREA.

PROTECTIVE CLOTHING:

AVOID CONTACT WITH EYES. WEAR CHEMICAL GOGGLES IF THERE IS THE POSSIBILITY OF CONTACT OR SPLASHING IN THE EYE. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WEAR CHEMICAL RESISTANT GLOVES AND OTHER CLOTHING TO KEEP EXPOSURE TO A MINIMUM. COVER ARMS AND LEGS. CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH CHEMICALS BECAUSE CONTACT LENSES MAY CONTRIBUTE TO THE SEVERITY OF AN EYE INJURY IN CASE OF EXPOSURE.

***** SECTION 9: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F. (49 DEG C.) BASED ON THE PRODUCT FLASH POINT AND VAPOR PRESSURE, SUITABLE STORAGE SHOULD BE PROVIDED IN ACCORDANCE WITH OSHA REGULATION 1910.106/ONTARIO OH&S REGULATION 851 SECTION 22. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN CLEANED OR RECONDITIONED.

ABBREVIATIONS USED:

OSHA-OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION;
IARC-INTERNATIONAL AGENCY FOR RESEARCH ON CANCER; LEL-LOWER EXPLOSIVE LIMITS;
UEL-UPPER EXPLOSIVE LIMITS; MG CU M-MILLIGRAMS PER METERS CUBED; MM-MILLIMETERS;
MPPCF-MILLIONS OF PARTICLES PER CUBIC FOOT; MSHA-MINE SAFETY AND HEALTH
ADMINISTRATION; NIOSH-NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY AND HEALTH;
WHMIS-WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION SYSTEM; H-HOURS; HR-HOURS;
NA-NOT APPLICABLE; NOT EST-NOT ESTABLISHED; NTP-NATIONAL TOXICOLOGY PROGRAM;
PB-LEAD; PEL-PERMISSIBLE EXPOSURE LEVEL; PPM-PARTS PER MILLION;
TCC/PM-TAG CLOSED CUP/PENSKY-MARTEN; RECM-RECOMMENDED; TLV-THRESHOLD LIMIT VALUES.
N.AV-NOT AVAILABLE; N.AP-NOT APPLICABLE; C-CELSIUS; F-FAHRENHEIT

SUPERIOR INDUSTRIES, INC.
MATERIAL SAFETY DATA SHEET

***** PREPARED BY SECTION

PREPARED BY: REGULATORY AFFAIRS DEPT.
MFG TELEPHONE NUMBER : (423) 899-0467
REVISION DATE : 11-09-12

DATE PRINTED : 11-09-12

***** DISCLAIMER SECTION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. SUPERIOR INDUSTRIES, INC. MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. SUPERIOR INDUSTRIES INC. FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THIS MATERIAL.

THIS MSDS COMPLIES WITH OSHA 1910.1200. SUPERIOR DOES NOT REPRESENT THAT IT MEETS ANY STATE-SPECIFIC REQUIREMENTS.

***** SECTION 1: PRODUCT IDENTIFICATION *****

MANUFACTURERS ADDRESS :6180 Airways Blvd; Chattanooga, Tn 37421
MFG TELEPHONE NUMBER : (423) 899-0467
24 HR EMERGENCY PHONE NO : 1-800-476-2072
CHEMICAL NAME OR FAMILY : COATINGS PRODUCT
FORMULA : NOT APPLICABLE
TRADE NAME :Re-Surf PART B Resin
REVISION DATE : 11-09-12
DATE PRINTED : 11-09-12

***** SECTION 2: HAZARDOUS INGREDIENTS *****

NAME	WT %				
COMMON(NA) : PROPRIETARY RESIN		TLV TWA	NOT	ESTAB	
CAS:TRADE SECRET		TLV STEL	NOT	ESTAB	
		OSHA PEL	NOT	ESTAB	
		CEILING	NOT	ESTAB	
		RECOMND	NOT	ESTAB	
COMMON(NA) : PROPRIETARY RESIN		TLV TWA	NOT	ESTAB	
CAS:TRADE SECRET		TLV STEL	NOT	ESTAB	
		OSHA PEL	NOT	ESTAB	
		CEILING	NOT	ESTAB	
		RECOMND	NOT	ESTAB	

THERE ARE NO SARA 313 CHEMICALS IN THIS PRODUCT

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH U.S. TSCA CHEMICAL SUBSTANCE INVENTORY REQUIREMENTS.

***** SECTION 3: PHYSICAL DATA *****

BOILING POINT: N.AV DEG F. (N.AV DEG C.)
VAPOR PRESSURE MM HG AT DEG F. (DEG C.): NA
VAPOR DENSITY (AIR = 1.0): NA
SPECIFIC GRAVITY: 1.10
PERCENT VOLATILE BY VOLUME: 0.00
EVAPORATION RATE (BUTYL ACETATE = 1): NA
SOLUBILITY IN WATER: NO
PH : N.AV
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.AV

***** SECTION 4: FIRE AND EXPLOSION HAZARD *****

FLASH POINT TCC/PM DEG F : 201
FLASH POINT TCC/PM DEG C : 93
LOWER EXPLOSIVE LIMIT : NA
UPPER EXPLOSIVE LIMIT : NA
AUTO IGNITION - DEG F : N.AV DEG C : N.AV
SENSITIVITY TO IMPACT : NONE
SENSITIVITY TO STATIC DISCHARGE : N.AV

EXTINGUISHING MEDIA: IN CASE OF FIRE, USE WATER SPRAY (FOG), ALCOHOL FOAM, DRY CHEMICAL, OR CARBON DIOXIDE.
WATER SPRAY MAY BE USED TO COOL CONTAINERS AND KEEP EXPOSED MATERIAL FROM BEING DAMAGED BY FIRE.

***** SECTION 4: FIRE AND EXPLOSION HAZARD *****CONTINUED*****

SPECIAL FIRE FIGHTING PROCEDURES:

FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS.
CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

CLOSED CONTAINERS MAY EXPLODE DUE TO BUILD UP OF PRESSURE WHEN EXPOSED TO HEAT.

***** SECTION 5: HEALTH HAZARD DATA *****

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:

IMMEDIATE EFFECTS (ACUTE):

OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND THROAT IRRITATION, EYE IRRITATION, SKIN IRRITATION, ALLERGIC SKIN REACTION, HARMFUL IF SWALLOWED, FATALITY IF SWALLOWED, RESPIRATORY TRACT IRRITATION, SKIN SENSITIZATION, DERMATITIS.

DELAYED EFFECTS (CHRONIC):

NONE KNOWN

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER.

CLOTHING: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH CLOTHING BEFORE REUSE. DESTROY CONTAMINATED SHOES.

INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.

SWALLOWING: IF SWALLOWED, INDUCE VOMITING IMMEDIATELY AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

***** SECTION 6: REACTIVITY DATA *****

THIS PRODUCT IS STABLE

CONDITIONS TO AVOID: NONE

INCOMPATIBILITY: NA

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON DIOXIDE/MONOXIDE

HAZARDOUS POLYMERIZATION: NONE

***** SECTION 7: SPILL OR LEAK PROCEDURES *****

VENTILATE AREA. AVOID BREATHING OF VAPORS. USE SELF-CONTAINED BREATHING APPARATUS OR AIRMASK FOR LARGE SPILLS IN A CONFINED AREA.

ELIMINATE IGNITION SOURCES.

REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

AVOID CONTACT WITH EYES.

***** SECTION 7: SPILL OR LEAK PROCEDURES

****CONTINUED****

WASTE DISPOSAL METHOD:

DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL, STATE, PROVINCIAL AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

***** SECTION 8: SPECIAL PROTECTION INFORMATION *****

RESPIRATORY PROTECTION:

UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ABOVE APPLICABLE LIMITS, NO RESPIRATOR IS REQUIRED. IF RESPIRATOR IS REQUIRED, THE APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) SHOULD BE WORN DURING APPLICATION. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

VENTILATION:

REQUIRED WHEN SPRAYING OR APPLYING IN CONFINED AREA.

PROTECTIVE CLOTHING:

AVOID CONTACT WITH EYES. WEAR CHEMICAL GOGGLES IF THERE IS THE POSSIBILITY OF CONTACT OR SPLASHING IN THE EYE. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WEAR CHEMICAL RESISTANT GLOVES AND OTHER CLOTHING TO KEEP EXPOSURE TO A MINIMUM. COVER ARMS AND LEGS.

CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH CHEMICALS BECAUSE CONTACT LENSES MAY CONTRIBUTE TO THE SEVERITY OF AN EYE INJURY IN CASE OF EXPOSURE.

***** SECTION 9: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F. (49 DEG C.) BASED ON THE PRODUCT FLASH POINT AND VAPOR PRESSURE, SUITABLE STORAGE SHOULD BE PROVIDED IN ACCORDANCE WITH OSHA REGULATION 1910.106/ONTARIO OH&S REGULATION 851 SECTION 22. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN CLEANED OR RECONDITIONED.

ABBREVIATIONS USED:

OSHA-OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION;
IARC-INTERNATIONAL AGENCY FOR RESEARCH ON CANCER; LEL-LOWER EXPLOSIVE LIMITS;
UEL-UPPER EXPLOSIVE LIMITS; MG CU M-MILLIGRAMS PER METERS CUBED; MM-MILLIMETERS;
MPPCF-MILLIONS OF PARTICLES PER CUBIC FOOT; MSHA-MINE SAFETY AND HEALTH
ADMINISTRATION; NIOSH-NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY AND HEALTH;
WHMIS-WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION SYSTEM; H-HOURS; HR-HOURS;
NA-NOT APPLICABLE; NOT EST-NOT ESTABLISHED; NTP-NATIONAL TOXICOLOGY PROGRAM;
PB-LEAD; PEL-PERMISSIBLE EXPOSURE LEVEL; PPM-PARTS PER MILLION;
TCC/PM-TAG CLOSED CUP/PENSKY-MARTEN; RECM-RECOMMENDED; TLV-THRESHOLD LIMIT VALUES.
N.AV-NOT AVAILABLE; N.AP-NOT APPLICABLE; C-CELSIUS; F-FAHRENHEIT

***** PREPARED BY SECTION

PREPARED BY: REGULATORY AFFAIRS DEPT.
MFG TELEPHONE NUMBER : (423) 899-0467
REVISION DATE : 11-09-12

DATE PRINTED : 11-09-12

***** DISCLAIMER SECTION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. Superior Industries, Inc. MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. Superior Industries, Inc. FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THIS MATERIAL.

THIS MSDS COMPLIES WITH OSHA 1910.1200. Superior DOES NOT REPRESENT THAT IT MEETS ANY STATE-SPECIFIC REQUIREMENTS.