

# Superior Industries, Inc.

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Material Identification

**Product ID:** 038.3302605  
Product Name: ChemKote 700 B Resin (Base)  
Product Use: Paint product.  
Date Published: 2012/11/09  
Revision Date: 2012/11/09

#### Company Identification

Superior Industries, Inc.  
6180 Airways Blvd.  
Chattanooga, TN 37421  
Manufacturer's Phone: 1-800-476-2072

**24-Hour Medical Emergency Phone:** 1-800-476-2072

### 2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Common Name CAS #	Approx Wt%	Chemical name
Trade Secret : PROPRIETARY RESIN	60 - 65	PROPRIETARY RESIN
Trade Secret : PROPRIETARY RESIN	15 - 20	PROPRIETARY RESIN
Trade Secret : PROPRIETARY ADDITIVE	15 - 20	PROPRIETARY ADDITIVE
Trade Secret : PROPRIETARY ADDITIVE	1 - 5	PROPRIETARY ADDITIVE

If this section is blank there are no hazardous components per OSHA guidelines.

### 3. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Emergency Overview:

This section not in use.

**This product contains ingredients that may contribute to the following potential acute health effects:**

#### Inhalation Effects:

Harmful if inhaled. May affect the brain, nervous system, or respiratory system, causing dizziness, headache, nausea or

respiratory irritation.

**Eye Contact:**

Corneal Injury/eye damage.

**Skin Contact:**

May cause skin burns. Contains a component which is a known or suspected skin sensitizer.

**Acute Ingestion:**

None known

**Other Effects:**

May cause central nervous system depression.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

May cause eye damage and pain. Contains a component which is a known or suspected skin sensitizer. May cause redness and blistering of skin. May cause kidney damage.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

## 4. FIRST AID MEASURES

**Inhalation:**

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention. If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention.

**Eye Contact:**

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

**Skin Contact:**

Remove contaminated shoes and discard. Remove contaminated clothing and launder before reuse. In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention.

**Ingestion:**

If swallowed, get medical attention immediately. If swallowed, do not induce vomiting. Give large quantities of water. If available, give several glasses of milk. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Medical conditions aggravated by exposure:** Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	220° F ( 104° C) TCC/PM
Lower explosive limit:	1 %
Upper explosive limit:	6 %
Autoignition temperature:	Not available.° F ( ° C)
Sensitivity to impact:	No.
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

Closed containers may explode due to build up of pressure when exposed to heat.

**Extinguishing media:**

In case of fire, use water spray (fog), alcohol foam, dry chemical, or carbon dioxide. Water spray may cause frothing when solid streams are directed on a fire. Spray of fog can be carefully used to cool containers and keep exposed material from being damaged by fire.

**Fire fighting procedures:**

Use water spray to cool nearby containers and structures exposed to fire. Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Action to be taken if material is released or spilled:**

Ventilate area. Avoid breathing of vapors. Use self-containing breathing apparatus or airmask for large spills in a confined area. Remove sources of ignition. Remove with inert absorbent and non sparking tools. Avoid contact with eyes.

## 7. HANDLING AND STORAGE

**Precautions to be taken in handling and storage:**

Keep away from heat, sparks, and flames. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

**Personal Protective Equipment****Eye and face protection:**

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

**Skin protection:**

Gloves: Neoprene or other nonporous. Neoprene or plastic apron and protective clothing covering exposed skin areas.

**Respiratory protection:**

If the product is sprayed, respiratory equipment should be used. Unless air monitoring demonstrates vapor/mist levels above applicable limits, no respirator is required. If respirator is required, the appropriate, properly fitted respirator (NIOSH approved) should be worn during application. Follow respirator manufacturers directions for respirator use.

**Ventilation**

Required when spraying or applying in confined area.

**Exposure Guidelines****OSHA Permissible Exposure Limits (PEL's)****ACGIH Threshold Limit Value (TLV's)**

Common Name CAS #	Approx Wt%	TWA	STEL	Ceiling limits	Skin designations
Trade Secret : PROPRIETARY ADDITIVE	1 - 5	300 PPM			

If this section is blank, no information is available.

## 9. PHYSICAL PROPERTIES

Odor: Normal for this product type.  
Physical State: Liquid  
pH: Not determined.  
Vapor pressure: Not determined. mmHG @ 0° F ( 20° C)  
Vapor density (air = 1.0): Not determined.  
Boiling point: 455° F ( 235° C)  
Solubility in water: Soluble  
Coefficient of water/oil distribution: Not determined.  
Density (weight per gallon): 9.587  
Specific gravity (water = 1): 1.15  
Evaporation rate (butyl acetate = 1.0): Not determined.

## 10. STABILITY AND REACTIVITY

Stability: This product is stable.  
Conditions to Avoid: None known.  
Incompatibility: Strong oxidizers. Acids or alkalies.  
Hazardous Polymerization: None anticipated.  
Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

**Sensitivity to static discharge:** Sensitivity to static discharge is not expected.

## 11. TOXICOLOGICAL INFORMATION

**Mutagens:**  
This material has demonstrated mutagenic activity in laboratory tests.

If this section is blank, no information is available.

## 12. ECOLOGICAL DATA

Not available at this time.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

**U.S. Department of Transportation**  
Proper Shipping Name: PAINT, NOT REGULATED

UN ID Number: NRPAIN

**49 CFR Hazardous Material Regulations Parts 100-180**

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

**International Air Transport Association:**

Proper Shipping Name: PAINT, NOT REGULATED  
UN ID Number: NRPAIN

**International Maritime Organization:**

Proper Shipping Name: PAINT, NOT REGULATED  
UN ID Number: NRPAIN

**15. REGULATORY INFORMATION**

**U.S. FEDERAL REGULATIONS:**

**SARA 311/312 Hazard Class:**

Acute: Yes  
Chronic: Yes  
Flammability: No  
Reactivity: No  
Sudden Pressure: No

**U.S. STATE REGULATIONS:**

**Pennsylvania Right To Know:**

PROPRIETARY ADDITIVE	Trade Secret
PROPRIETARY ADDITIVE	Trade Secret
PROPRIETARY RESIN	Trade Secret
PROPRIETARY RESIN	Trade Secret

**Rule 66 status of product** Not photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories**

**TSCA Inventory:** All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:** Not all components in this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION**

**HMIS Codes**

Health: 3  
Flammability: 1  
Reactivity: 1

Product ID: 038.3302605

**PPE:**

X - See Section 8 for Personal Protective Equipment (PPE).

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substance Chemical Administration, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Superior assumes no obligation or liability for use of this information. UNLESS SUPERIOR AGREES OTHERWISE IN WRITING, SUPERIOR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPERIOR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

# Superior Industries, Inc.

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Material Identification

**Product ID:** 038.3301399  
Product Name: ChemKote 700 A (Hardener)  
Product Use: Paint product.  
Date Published: 2012/11/09  
Revision Date: 2012/11/09

#### Company Identification

Superior Industries, Inc.  
6180 Airways Blvd.  
Chattanooga, TN 37421  
Manufacturer's Phone: 1-800-476-2072

**24-Hour Medical Emergency Phone:** 1-800-476-2072

### 2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Common Name CAS #	Approx Wt%	Chemical name
BENZYL ALCOHOL 100-51-6	50 - 55	Benzyl alcohol
Trade Secret : PROPRIETARY RESIN	40 - 45	PROPRIETARY RESIN

If this section is blank there are no hazardous components per OSHA guidelines.

### 3. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Emergency Overview:

This section not in use.

**This product contains ingredients that may contribute to the following potential acute health effects:**

#### Inhalation Effects:

May be harmful if inhaled.

#### Eye Contact:

Corneal Injury/eye damage.

**Skin Contact:**

May cause moderate skin irritation.

**Acute Ingestion:**

May be harmful if swallowed.

**Other Effects:**

None known

**This product contains ingredients that may contribute to the following potential chronic health effects:**

May cause eye damage and pain. May cause redness and blistering of skin.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

## 4. FIRST AID MEASURES

**Inhalation:**

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

**Eye Contact:**

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

**Skin Contact:**

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention. Remove contaminated shoes and discard. Remove contaminated clothing and launder before reuse.

**Ingestion:**

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If swallowed, get medical attention immediately.

**Medical conditions aggravated by exposure:** Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	219° F ( 104° C) TCC/PM
Lower explosive limit:	Not available. %
Upper explosive limit:	Not available. %
Autoignition temperature:	Not available.° F ( ° C)
Sensitivity to impact:	No.
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

Closed containers may explode due to build up of pressure when exposed to heat.

**Extinguishing media:**

In case of fire, use water spray (fog), alcohol foam, dry chemical, or carbon dioxide. Water spray may cause frothing when solid streams are directed on a fire. Spray of fog can be carefully used to cool containers and keep exposed material from being damaged by fire.



**Fire fighting procedures:**

Use water spray to cool nearby containers and structures exposed to fire. Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

**6. ACCIDENTAL RELEASE MEASURES****Action to be taken if material is released or spilled:**

Ventilate area. Avoid breathing of vapors. Use self-containing breathing apparatus or airmask for large spills in a confined area. Remove sources of ignition. Remove with inert absorbent and non sparking tools. Avoid contact with eyes.

**7. HANDLING AND STORAGE****Precautions to be taken in handling and storage:**

Keep away from heat, sparks, and flames. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22.

**8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS****Personal Protective Equipment****Eye and face protection:**

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

**Skin protection:**

Gloves: Neoprene or other nonporous. To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If the product is sprayed, respiratory equipment should be used. Unless air monitoring demonstrates vapor/mist levels above applicable limits, no respirator is required. If respirator is required, the appropriate, properly fitted respirator (NIOSH approved) should be worn during application. Follow respirator manufacturers directions for respirator use.

**Ventilation**

Required when spraying or applying in confined area.

**Exposure Guidelines****OSHA Permissible Exposure Limits (PEL's)****ACGIH Threshold Limit Value (TLV's)**

Common Name CAS #	Approx Wt%	Supplier Recommended
BENZYL ALCOHOL 100-51-6	50 - 55	10 PPM

If this section is blank, no information is available.

**9. PHYSICAL PROPERTIES**

Odor:	Normal for this product type.
Physical State:	Liquid
pH:	Not determined.
Vapor pressure:	Not determined. mmHG @ 86° F ( 30° C)
Vapor density (air = 1.0):	3.7
Boiling point:	400° F ( 204° C)
Solubility in water:	Insoluble.
Coefficient of water/oil distribution:	Not determined.
Density (weight per gallon):	8.83
Specific gravity (water = 1):	1.06
Evaporation rate (butyl acetate = 1.0):	Not determined.

## 10. STABILITY AND REACTIVITY

Stability:	This product is stable.
Conditions to Avoid:	None known.
Incompatibility:	Acids or alkalies.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Ammonia compounds. Nitrogen compounds. Aldehydes.

**Sensitivity to static discharge:** Sensitivity to static discharge is not expected.

## 11. TOXICOLOGICAL INFORMATION

If this section is blank, no information is available.

## 12. ECOLOGICAL DATA

Not available at this time.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

Proper Shipping Name:	PAINT, NOT REGULATED
UN ID Number:	NRPAIN

### 49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

### International Air Transport Association:

Proper Shipping Name:	PAINT, NOT REGULATED
UN ID Number:	NRPAIN

**International Maritime Organization:**

Proper Shipping Name: PAINT, NOT REGULATED  
UN ID Number: NRPAIN

**15. REGULATORY INFORMATION**

**U.S. FEDERAL REGULATIONS:**

**SARA 311/312 Hazard Class:**

Acute: Yes  
Chronic: Yes  
Flammability: No  
Reactivity: No  
Sudden Pressure: No

**U.S. STATE REGULATIONS:**

**Pennsylvania Right To Know:**

PROPRIETARY RESIN  
BENZYL ALCOHOL

Trade Secret  
100-51-6

**Rule 66 status of product** Not photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories**

**TSCA Inventory:** All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:** Not all components in this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION**

**HMIS Codes**

**Health:** 3  
**Flammability:** 1  
**Reactivity:** 1  
**PPE:** X - See Section 8 for Personal Protective Equipment (PPE).

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substance Chemical Administration, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term

exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Superior assumes no obligation or liability for use of this information. UNLESS SUPERIOR AGREES OTHERWISE IN WRITING, SUPERIOR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPERIOR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.