

MATERIAL SAFETY DATA SHEET

WaterTron Epoxy XLT

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WATERTRON EPOXY XLT PART A POURABLE

MANUFACTURER: Superior Industries
STREET ADDRESS: 6180 Airways Blvd.
CITY, STATE, ZIP: Chattanooga, TN 37421

INFORMATION PHONE: 423-899-0467
FAX PHONE: 423-899-0421
WEBSITE: www.superior-industries.com

PREPARED BY: Compliance Department
DATE REVISED: 10/12/12

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A	25068-38-6	NONE	NONE	NONE	
ALKYL GLYCIDYL ETHER	68609-97-2	NONE	NONE	NONE	
BENZYL ALCOHOL EXTENDER	100-51-6	NONE	NONE	NONE	
	NON HAZARDOUS IN LIQUID FORM	20mg/m3	20mg/m3	20mg/m3	

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR are present.

SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: VISCOUS LIQUID – NEGLIGIBLE ODOR
BOILING POINT OR RANGE: 200 TO 401F
VAPOR DENSITY (AIR = 1): N/A
SPECIFIC GRAVITY (H2O = 1): 1.4
EVAPORATION RATE: N/A
SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 3 NOTES:

SECTION 4: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, (% by volume) UPPER: not available
LOWER: not available
FLASH POINT: 200+F
METHOD USED:
SETA FLASH
EXTINGUISHING MEDIA:
FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG
SPECIAL FIRE FIGHTING PROCEDURES:
DO NOT ENTER CONFINED FIRE ARE WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.
UNUSUAL FIRE AND EXPLOSION HAZARDS:
NO UNUSUAL FIRE HAZARDS KNOWN.

SECTION 4 NOTES:

SECTION 5: STABILITY AND REACTIVITY

STABILITY:
STABLE
CONDITIONS TO AVOID (STABILITY):
AVOID EXCESSIVE HEAT OR OPEN FLAMES
INCOMPATIBILITY (MATERIAL TO AVOID):
CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:
CO2, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.
HAZARDOUS POLYMERIZATION:
WILL NOT OCCUR

SECTION 5 NOTES:

SECTION 6: HAZARDS IDENTIFICATION

MATERIAL SAFETY DATA SHEET

WaterTron Epoxy XLT

HMIS HAZARD CLASSIFICATION

HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: B

POTENTIAL HEALTH EFFECTS

EYES:

MAY CAUSE IRRITATION TO THE NOSE, THROAT, OR MUCOUS MEMBRANES.

SKIN:

MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.

INGESTION:

THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION:

NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT, OR MUCOUS MEMBRANES.

HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR.

EYES: INJURY IS UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

SECTION 7: FIRST AID MEASURES

EYES:

FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION:

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE IMMEDIATELY CONSULT WITH A PHYSICIAN.

INHALATION:

REMOVE VICTIM TO FRESH AIR AREA AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 7 NOTES:

SECTION 8: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBANT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

SECTION 8 NOTES:

SECTION 9: WASTE DISPOSAL

WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

SECTION 10: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFOR, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CANNOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

SECTION 10 NOTES:

SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

MATERIAL SAFETY DATA SHEET

WaterTron Epoxy XLT

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR.

VENTILATION:

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES, NEOPRENE OR RUBBER.

EYE PROTECTION:

SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SECTION 11 NOTES:

SECTION 12: DISCLAIMER

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

MATERIAL SAFETY DATA SHEET

WaterTron Epoxy XLT

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WATERTRON EPOXY XLT PART B

MANUFACTURER: Superior Industries
STREET ADDRESS: 6180 Airways Blvd.
CITY, STATE, ZIP: Chattanooga, TN 37421

INFORMATION PHONE: 423-899-0467
FAX PHONE: 423-899-0421
WEBSITE: www.superior-industries.com

PREPARED BY: Compliance Department
DATE REVISED: 10/12/12

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
COMPLEX POLYALIPHATIC AMINE SYSTEM	UNKNOWN	NONE	NONE	NONE	
*PHENOL	108-95-2	5PPM	5PPM	10PPM	
5					
M-XYLENE DIAMINE	1477-55-0	NONE	.1mg/m3	NONE	
BENZENE-1, 3-DIMETHANEAMINE/PHENOL/ FORMALDAHYDE	57214-10-5	NONE	NONE	NONE	
EXTENDER	NON HAZARDOUS IN LIQUID FORM	20mg/m3	20mg/m3	20mg/m3	
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE	

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: AMBER VISCOUS LIQUID WITH AMINE ODOR
BOILING POINT OR RANGE: 401F
VAPOR DENSITY (AIR = 1): N/A
SPECIFIC GRAVITY (H2O = 1): 1.4
EVAPORATION RATE: N/A
SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 3 NOTES:

SECTION 4: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: not available
(% by volume) LOWER: not available
FLASH POINT: 200+F
METHOD USED:
SETA FLASH
EXTINGUISHING MEDIA:
FOAM, ALCOHOL FOAM, CO2, WATER FOG
SPECIAL FIRE FIGHTING PROCEDURES:
TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.
UNUSUAL FIRE AND EXPLOSION HAZARDS:
NONE KNOWN.

SECTION 4 NOTES:

SECTION 5: STABILITY AND REACTIVITY

STABILITY:
STABLE
CONDITIONS TO AVOID:
AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.
INCOMPATIBILITY (MATERIAL TO AVOID):
AVOID CONTACT WITH STRONG OXIDIZING AGENTS , MINERAL ACIDS, AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:
CO, CO2, NOX

HAZARDOUS POLYMERIZATION:
WILL NOT OCCUR.

MATERIAL SAFETY DATA SHEET

WaterTron Epoxy XLT

SECTION 5 NOTES:

SECTION 6: HAZARDS IDENTIFICATION

HMIS HAZARD CLASSIFICATION

HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

EYES:

WILL CAUSE BURNS TO THE EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.

SKIN:

WILL CAUSE BURNS TO THE SKIN.

INGESTION:

LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

INHALATION:

HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.

HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

SECTION 7: FIRST AID MEASURES

EYES:

IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE LIFTING UPPER AND LOWER LIDS.

GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET

MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION

IMMEDIATELY.

INHALATION:

REMOVE TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 7 NOTES:

SECTION 8: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBANT AND PLACE IN DISPOSAL CONTAINERS.

SECTION 8 NOTES:

SECTION 9: WASTE DISPOSAL

WASTE DISPOSAL METHOD:

DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 10: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL SAFETY DATA SHEET

WaterTron Epoxy XLT

RESPIRATORY PROTECTION:

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH PROOF GOGGLES OR GLASSES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

CLEAN BODY COVERING CLOTHING AS WELL AS APRON FOOTWEAR OR OTHER EQUIPMENT SHOULD BE USED AS DEEMED NECESSARY TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SECTION 11 NOTES:

SECTION 12: DISCLAIMER

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.