

**SUPERIOR INDUSTRIES, INC.  
MATERIAL SAFETY DATA SHEET**

NPCA

**FOR COATINGS, RESINS AND RELATED MATERIALS**  
(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

**Date Issued** 11/27/12

**SECTION I**

**MANUFACTURERS NAME**

Superior Industries, Inc.

**STREET ADDRESS**

6180 Airways Blvd.

**CITY, STATE, AND ZIP CODE**

Chattanooga, TN 37421

**EMERGENCY TELEPHONE NUMBER**

1-800-476-2072

**PRODUCT CLASS**

Surface Pro 600 ( Asphalt Pothole Patch)

**MANUFACTURER'S CODE**

IDENTIFICATION

75633

**TRADE NAME**

SUPERIOR

**SECTION II- HAZARDOUS INGREDIENTS**

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE
PETROLEUM ASPHALT CAS # - 8052-42-4	<30%		5.0		
CRUSHED STONE CAS #- 1317-65-3	<80%	10*			
CELLULOSE FIBER CAS #- 9004-34-6	<10%	10*			
PETROLEUM DISTILLATE CAS #- 68476-34-6	<6%	800			
FATTY & RESIN ACIDS CAS #- 8002-26-4	<4%	**			

ADDITIONAL INFORMATION-\* AS RESPIRABLE DUST \*\* NOT ESTABLISHED.

**Hazardous Materials Identification System (HMIS)**

Health  
1

Flammability  
2

Reactivity  
0

Personal Protection  
G

**SECTION III – PHYSICAL DATA**

BOILING RANGE: 300 °F - 390°F VAPOR DENSITY  HEAVIER  LIGHTER, THAN AIR

EVAPORATION RATE  FASTER  SLOWER, THAN ETHER PERCENT VOTILE BY VOLUME 7.5 % WEIGHT PER GALLON BY VOLUME 14 LBS

**SECTION IV – FIRE AND EXPLOSION HAZARD DATA**

DOT CATEGORY - N/R

FLASH POINT- 105°F Minimum

EXTINGUISHING MEDIA-

CO2, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS-  
TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED

SPECIAL FIRE FIGHTING PROCEDURES-

WEAR SELF CONTAINED BREATHING APPARATUS.

WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

---

### SECTION V – REACTIVITY DATA

---

STABILITY:  UNSTABLE

STABLE

CONDITIONS TO AVOID: HEAT, FLAMES, STRONG  
OXIDIZERS

INCOMPATIBILITY (MATERIALS TO AVOID): CARBON OXIDES

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

HAZARDOUS POLYMERIZATION:  MAY OCCUR

WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

---

### SECTION VI-HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE-ACUTE: SKIN: PROLONGED /REPEATED CONTACT MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS.-EYES: MAY CAUSE SEVERE IRRITATION, REDNESS TEARING AND BLURRED VISION.-INHALATION: MAY CAUSE DIZINESS, WEAKNESS, HEADACHE, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.-INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

EMERGENCY FIRST AID PROCEDURE-SKIN: REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA. WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. EYES:FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXIGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION AND SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM AND QUIET. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL.

---

### SECTION VII – SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

---

### SECTION VIII – SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: RUBBER SHOULD BE USED.

EYE PROTECTION: SAFETY GLASSES SHOULD BE USED.

OTHER PROTECTIVE EQUIPMENT: FACE SHIELD

---

### SECTION IX – REGULATORY INFORMATION

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY CLOSED.