MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION Formula: Proprietary HMIS Rating:

Product Name: Rust Magic

Product Number: 964502 Ρ S s D

Date Prepared: 11/27/12 Emergency Phone: (800) 476-2072 nformation Phone: (423) 899-0467

0-Minimal 1- Slight 2- Moderate 3- Serious 4- Extreme HEALTH: 2 FIRE: 0 REACTIVITY: 1 Personal Protection: B

roduct Type: Liquid	Emer
Supplier's Name: Superior Industries, Inc.	Infor
Supplier's Address: P.O. Box 8, Chattanooga, TN 37401	
D.O.T. Shipping Description: Compounds, cleaning liquid, I	N.O.S.

SECTION II · INGREDIENTS									
CHEMICAL NAME	CAS #	313/Chem	Skin	Carcinogen	PEL	TWA/TLV			
Ethanedioic Acid	144-62-78	NO	NO	NO	1 mg/m ³	1 mg/m ³			
Isopropyl Alcohol	67-63-0	NO	NO	NO	400 ppm	400 ppm			
Dipropylene Glycol Methyl Ether	34590-94-8	NO	NO	NO	100 ppm	100 ppm			

SECTION III · PHYSICAL DATA

Boiling Point: ~ 212° F pH: 2 Solubility In Water: Complete Appearance/Odor: Clear liquid with mild acidic odor Total VOC %: 0.14%

Vapor Density(Air=1): >1 Percent Volatile by Volume: 74% Specific Gravity (H₂O=1): 1.01

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point: none to boiling Extinguishing Media: Not applicable. Special Fire Fighting Procedures: None needed. Unusual Fire and Explosion Hazards: None known.

SECTION V · REACTIVITY DATA

Stability: Material stable under ordinary conditions of use and storage. Heat will contribute to instability. Hazardous Polymerization: Will not Occur. Incompatibility: Alkalis, chlorites, hypochlorites, oxidizing agents, furfuryl alcohol, and silver compounds. Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN. For Industrial and Institutional use only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120° F.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause severe irritation, resulting in corneal injury.

Skin: Causes irritation. May cause rare chemical burns and hypocalcemia.

Inhalation: Inhalation of mist causes irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause damage to mucous membranes, headache, nervousness, cough, vomiting, emaciation, back pain, and weakness.

Ingestion: Can cause gastrointestinal irritation, ulcerations of the mouth, nausea, vomiting of blood, shock, convulsions, and cardiovascular collapse. Aspiration of material into the lungs can cause chemical pneumonitis.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

Skin: Wash immediately with soap and plenty of water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do NOT induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep concentration of Section II ingredients below acceptable limits. Protective Gloves: Use chemical resistant gloves if hand contact will be made.

Eye Protection: It is recommended to always wear safety glasses or chemical proof goggles when working with any chemical.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws

WASTE DISPOSAL METHOD: Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.

MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

Product Name: Zin-Kote 601 Product Number: 90058 Product Type: AEROSOL Supplier's Name: Superior Industries, Inc. Supplier's Address: P.O. Box 8, Chattanooga, TN 37421 D.O.T. Hazard Class: CONSUMER COMMODITY · ORM-D Formula: Proprietary Date Prepared: 11/27/12 Emergency Phone/: (800) 476-2072 Information Phone: (423) 899-0467

 HMIS Rating (Based on Aerosol Conc.):

 0-Minimal
 1- Slight
 2- Moderate

 3- Serious
 4- Extreme

 HEALTH:
 1 FIRE:
 3 REACTIVITY:
 1

 Personal Protection:
 B

	SECTION II · INGREDIENTS								
CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TWA/TLV		
Petroleum Distillate Modified Oil (Mineral Spirits)	64742-89-8 8052-41-3	20-40 10-20	NO NO	NO NO	NO NO	400 ppm N/E	400 ppm N/E		
Zinc Dust	7440-66-6	10-20	YES	NO	NO	15mg/cuM (Dust)	15mg/cuM (Dust)		
Liquified Petroleum Gas	68476-85-7	20-40	NO	NO	NO	1000 ppm	1000 ppm		

SECTION III · PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only: Boiling Point: 160°F pH: N/A Solubility In Water: Negligible Appearance/Odor: Gray Viscous Liquid, Solvent Odor Data Below Based On Total Contents: Vapor Pressure of can (psig @70°F): 62 Total VOC %: 75%

Vapor Density(Air=1): >1 Specific Gravity (H₂O=1)@75°F: 1.105

SECTION IV · FIRE AND EXPLOSION DATA Flammability (as per USA Flame Projection Test): Extremely Flammable Spray

Flash Point (of Concentrate Only): 80°F Extinguishing Media: Foam, CO₂, Dry Media

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing. Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.

SECTION V · REACTIVITY DATA

Stability: Material Stable. Hazardous Polymerization: Will not Occur. Incompatibility: Avoid contact with strong oxidizing agents.

Incompatibility: Avoid contact with strong oxidizing agents. Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN. For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120° F.

NFPA Code 30B Rating: Level 3 Aerosol.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged contact may cause irritation.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

Protective Gloves: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

Eye Protection: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.